


RING TYPE INSULATED TERMINAL



CABLE SIZE	STUD SIZES AVAILABLE	COLOR
1.5 TO 2.5	3MM,4MM,5MM & 6MM	RED
2.5 TO 4 MM	3MM,4MM,5MM & 6MM	BLUE
4MM TO 6MM	3MM,4MM,5MM & 6MM	YELLOW

▶▶ VINYL INSULATED PIN TERMINAL



- MATERIAL: COPPER
- INSULATION MATERIAL: VINYL (PVC)
- PLATING: ELECTRO TIN PLATED
- MAX. ELECTRICAL RATING: 600VOLT
- MAX. OPERATING TEMPERATURE: 75°C (167°F)



ITEM NO.	Ød1 (mm)	Ød (mm)	L (mm)	L1 (mm)	INSULATION COLOR	WIRE RANGE A.W.G. (mm ²)	PACKING PER BAG
VPT 1-10	1.9	4.1	20.5	10.5	RED	22 ~ 16	1000PCS OR 100PCS
VPT 1	1.9	4.1	22.5	10.5		(0.5 ~ 1.5)	
VPT 2-10	1.9	4.5	21.0	11.0	BLUE	16 ~ 14	
VPT 2	1.9	4.5	23.0	11.0		(1.5 ~ 2.5)	
VPT 5	2.7	6.8	28.0	13.0	YELLOW	12 ~ 10 (4.0 ~ 6.0)	

»» VINYL INSULATED BLADE TERMINAL WITH COPPER-SLEEVE



- MATERIAL: COPPER
- INSULATION MATERIAL: VINYL (PVC)
- PLATING: ELECTRO TIN PLATED
- MAX. ELECTRICAL RATING: 600VOLT
- MAX. OPERATING TEMPERATURE: 75°C (167°F)

ITEM NO.	W (mm)	L (mm)	L1 (mm)	L2 (mm)	Ød (mm)	INSULATION COLOR	WIRE RANGE A.W.G. (mm ²)	PACKING PER BAG
VBL 1-10-C	2.3	20.7	10.2	10.5	4.5	RED	22 ~ 16 (0.5 ~ 1.5)	1000PCS OR 100PCS
VBL 1-11-C	3.0	21.6	11.1					
VBL 1-14-C	3.0	25.0	14.5					
VBL 1-18-C	2.3	28.7	18.2					
VBL 2-9-C	2.8	19.5	9.0	10.5	5.2	BLUE	16 ~ 14 (1.5 ~ 2.5)	
VBL 2-13-C	2.3	23.5	13.0					
VBL 2-18-C	2.3	28.7	18.2					
VBL 5-10-C	2.8	22.5	10.0	12.5	6.8	YELLOW	12 ~ 10 (4.0 ~ 6.0)	
VBL 5-18-C	3.0	30.7	18.2					

Cord End Terminals (INSULATED WIRE END SLEEVES)

