




▶▶ VINYL INSULATED FEMALE DISCONNECTOR



- MATERIAL: BRASS
- INSULATION MATERIAL: VINYL (PVC)
- PLATING: ELECTRO TIN PLATED
- MAX. ELECTRICAL RATING: 300VOLT
- MAX. OPERATING TEMPERATURE: 75°C (167°F)

ITEM NO.	W (mm)	L (mm)	L1 (mm)	L2 (mm)	Ød (mm)	TAB. THICKNESS	INSULATION COLOR	WIRE RANGE A.W.G. (mm ²)	PACKING PER BAG
VD 1-2.8F5	3.2	18.4	6.4	10.0	4.0	0.5	RED	22 ~ 16 (0.5 ~ 1.5)	1000PCS OR 100PCS
VD 1-2.8F8	3.2	18.4	6.4			0.8			
VD 1-4.8F5	5.0	19.0	6.4			0.5			
VD 1-4.8F8	5.0	19.0	6.4			0.8			
VD 1-6.3F	6.6	21.0	7.8			0.8			
VD 1-8F	8.2	23.0	10.0			0.8			
VD 2-2.8F5	3.2	18.4	6.4	10.0	4.6	0.5	BLUE		
VD 2-2.8F8	3.2	18.4	6.4			0.8			
VD 2-4.8F5	5.0	19.0	6.4			0.5			
VD 2-4.8F8	5.0	19.0	6.4			0.8			
VD 2-6.3F	6.6	21.0	7.8			0.8			
VD 2-8F	8.2	23.0	10.0			0.8			
VD 5-6.3F	6.6	24.0	7.8	13.0	5.5	0.8	YELLOW		
VD 5-9.5F	10.0	29.0	12.0					1.1	